



COSHH and the woodworking industries

Woodworking Sheet No 6 (rev)

Introduction

This Information Sheet is one of a series prepared by HSE's Woodworking National Interest Group. Its purpose is to provide advice to employers on the application of the Control of Substances Hazardous to Health (COSHH) Regulations 1999¹ to the woodworking industry.

What are the Regulations about?

The purpose of the COSHH Regulations is to protect people from the risk to their health caused by exposure to hazardous substances at work.

What is a substance hazardous to health?

For the purposes of COSHH, these are:

- chemicals labelled as 'very toxic', 'toxic', 'harmful', 'irritant' or 'corrosive';
- substances with occupational exposure limits (OELs) (listed in HSE Guidance Note EH40²);
- harmful micro-organisms;
- any kind of dust in a substantial concentration;
- any other substance with comparable hazards to people's health.

Does COSHH apply to the woodworking industry?

Yes. Wood dust, resins used in some particle boards, adhesives, paint strippers, 2-pack polyurethane paints/varnishes, stains and wood preservatives are examples of substances used in the woodworking industry which may be hazardous to health (see Table 1).

How can employees be exposed to these substances?

Substances hazardous to health can enter the body by a number of routes. These include inhalation, ingestion and absorption through the skin.

What types of substance can be inhaled?

Wood dust is the most obvious example.³ A maximum exposure limit (MEL) of 5 mg/m³ has been set for both hardwood and softwood dusts. This means that exposure to wood dust must be reduced so far as is reasonably practicable, and must not in any case exceed the MEL. Particle boards, eg chipboard and medium-density fibreboard (MDF), are composed largely of softwood and the dust produced from machining them should be treated as such.

Other hazardous substances commonly found in woodworking which can be inhaled and have occupational exposure limits include 1,1,1-trichloroethane (in some adhesives); dichloromethane⁴ (in paint strippers and adhesives); isocyanates (in 2-pack polyurethane paints and varnishes); certain glycol ethers which may be present in stains and varnishes; and arsenic pentoxide (in water-based wood preservatives).

Some organic wood preservatives contain substances which have occupational exposure limits. These include lindane, pentachlorophenol, tributyl-tin-oxide and white spirit.

What could be ingested?

Wood preservatives are a good example. Ingestion is usually accidental and normally occurs because protective clothing is not used and personal hygiene is of a low standard. It can occur by biting contaminated fingernails, eating or smoking with contaminated hands or wearing contaminated clothing.

What could pass through the skin?

Some wood preservatives, eg lindane, pentachlorophenol and many solvents, eg toluene and dichloromethane can be absorbed through the skin and cause a variety of ill-health effects. This route of exposure needs to be considered carefully, systems of work modified and protective equipment such as gloves, overalls etc provided as necessary.

What about skin contact?

Other substances cause local skin effects such as dermatitis, eg epoxy resins, timber preservatives and some woods. A high standard of hygiene and protective clothing is required.

Some people can be allergic or sensitised to certain substances. Does this have to be taken into account?

Yes. For example, some woods are recognised as causing skin or respiratory irritation. Iroko can cause dermatitis and western red cedar can cause nasal irritation or asthma in susceptible individuals. Other woods can also give rise to allergic reactions.⁵

Many types of glues and resins, and some isocyanate based paints and varnishes have caused occupational asthma.⁶

What is the first thing that should be done to comply with COSHH?

Employers must carry out an assessment of all work activity which may expose their employees to any hazardous substances, and of all the precautions needed to protect their health. They must identify the hazard, the level of risk and

also any control measures needed. This will depend not only on the substance, but also on the working methods, route of exposure etc. The assessment should normally be recorded and must be regularly reviewed.

How do I go about making an assessment?

Follow the guidance in *A step by step guide to COSHH assessment*.⁷ To encourage part-ownership and direct relevance to the actual working conditions the assessments should, ideally, be carried out by the employer's own staff. If you decide to get an outside consultant's help, satisfy yourself that they can carry out the work competently.

How am I expected to know what is hazardous?

Look at the labels on product containers and suppliers' health and safety sheets and check HSE guidance. Also check with your trade association, as many have prepared guidance for their members.

What should be done about the risks identified?

First consider whether you can eliminate the risk by substitution and/or changing your production or treatment process. Is the least hazardous product being used for the job? For example, it is often possible to substitute solvent-based products for water-based ones. Stains containing potentially harmful glycol ethers can be substituted by less harmful types.

If elimination of the risk is not possible then it must be adequately controlled by, whenever possible, enclosing the process or by providing local exhaust ventilation.

When is air sampling necessary?

You may need to do air sampling during the assessment if you are not sure whether employees' exposure to a substance is below the occupational exposure limit, or if you are not sure whether the control measures are working properly.

In the case of dust, there are other techniques which can help you decide whether the control is adequate. Look around the machine to observe the presence of dust. Use a dust lamp to find out if the dust is being captured by the exhaust extraction system.⁸ Thoroughly examine the extraction system to see whether it leaks and meets its designed performance criteria.⁹ You may need to do routine air sampling once controls are in place to check that they are working properly.^{10,11}

Is dust extraction needed at woodworking machines?

Yes. At the great majority of woodworking machines the levels of dust produced, from both hardwood and softwood, will be above the MEL. Exposure to dust can be adequately controlled by a properly designed and maintained extraction system.^{9,12,13} Always obtain a full commissioning report with performance figures if you have a new extraction system installed. That way you ensure that it performs adequately from the outset.

How about portable machines like orbital sanders and circular saws?

Yes. They too need control. Several suppliers of portable machines have designed them to be used with integral dust extraction or connected to mobile vacuum extractor units. Alternatively, down draught work benches or booths fitted with local exhaust ventilation can be used.

Can't employees just wear a respirator?

No. The COSHH Regulations require control of exposure to the hazardous substance at source wherever possible. If control cannot be achieved by engineering controls alone then personal protective equipment (PPE), such as dust respirators, have to be used. These should always be in addition to engineering controls and not substitutes for them.

PPE may be necessary during routine short-term maintenance operations, such as cleaning ventilation plant and bag filters or entry into treatment vessels.

If the use of a respirator is necessary, which type can be used?

It should be selected from equipment that carries the European Community mark of conformity (the CE mark) and be appropriate to adequately control the exposure to the substance creating the risk.^{14,15}

What is health surveillance?

Health surveillance is any activity which involves obtaining information about an employee's health and which assists in protecting that employee from health risks at work.¹⁶ A simple record must be kept of any surveillance carried out.

Under COSHH it is required where:

- employees are exposed to a substance linked to a particular disease or adverse health effect; **and**
- there is a reasonable likelihood under the conditions of the work of the effect occurring; **and**
- there are valid techniques for detecting the disease or adverse effect.

It may involve examinations by a doctor or a trained nurse. But in some cases trained supervisors could, for example, check employees' skin for dermatitis, or administer a questionnaire asking about breathing difficulties where the work involves substances likely to cause asthma.

The following are examples of situations where health surveillance may be appropriate:

- 1 Exposure to substances of known systemic toxicity, eg organophosphorus and copper-chrome-arsenic wood preservatives or diethylene dioxide used for paint stripping. As well as keeping health records you should arrange for appropriate laboratory or clinical investigations, including biological monitoring, eg urine tests for the presence of arsenic. This should

be carried out by or under the supervision of a doctor.^{17,18}

- 2 Exposure to organic solvent-based preservatives, eg containing tributyl-tin-oxide, pentachlorophenol or lindane. These substances can be taken into the body by inhalation or skin absorption. Health records are required and in certain circumstances biological monitoring may be needed.
- 3 Exposure to substances known to cause occupational asthma and respiratory sensitisers, eg isocyanates, epoxy resin curing agents and western red cedar dusts.¹⁹ Health surveillance will involve the keeping of health records as well as enquiries seeking evidence of respiratory symptoms.
- 4 Exposure to substances known to cause severe dermatitis and skin sensitisation, eg epoxy resins and organic solvents such as dichloromethane or organic solvent-based wood preservatives. Skin inspections should be carried out at regular intervals by a responsible person.
- 5 Exposure to substances which are known or suspected carcinogens, eg hardwood dust and inorganic arsenic compounds. In the case of hardwood dust, it is doubtful whether nasal cancer could be detected at an early enough stage for treatment to be effective. Health surveillance would be restricted to the keeping of health records.

Note: Inorganic arsenic compounds found in wood preservatives can cause skin cancer and regular skin inspections may be necessary.

Will special training need to be provided?

Yes. Information, instruction and training is vital. Employers must provide training for employees who are exposed to hazardous substances at work. The employees should understand the nature and degree of risks to health which could arise as a consequence of exposure and the precautions which must be taken.

Reading list and references

- 1 *General COSHH ACOP and Carcinogens ACOP and Biological Agents ACOP. Control of Substances Hazardous to Health Regulations 1999. Approved Codes of Practice L5* HSE Books 1999 ISBN 07176 1670 3
- 2 *Occupational Exposure Limits* Guidance Note EH40 (issued annually) HSE Books 2000 ISBN 0 7176 1730 0
- 3 *Wood dust: Hazards and precautions* WIS1(rev1) HSE Books 1997
- 4 *Health risks during furniture stripping using dichloromethane (DCM)* WIS19 HSE Books 1992
- 5 *Toxic woods* WIS30 HSE Books 1995
- 6 *Preventing asthma at work - how to control respiratory sensitisers* L55 HSE Books 1994 ISBN 0 7176 0661 9

7 *A step by step guide to COSHH assessment* HSG97 HSE Books 1993 ISBN 0 7176 1446 8

8 *Assessment and control of wood dust: Use of the dust lamp* WIS12 HSE Books 1991

9 *Maintenance, examination and testing of local exhaust ventilation* HSG54 HSE Books 1998 ISBN 0 7176 1485 9

10 *Monitoring strategies for toxic substances* HSG173 HSE Books 1997 ISBN 0 7176 1411 5

11 *General methods for the sampling and gravimetric analysis of respirable and total inhalable dust* MDHS14/3 HSE Books 2000 ISBN 0 7176 1749 1

12 *An introduction to local exhaust ventilation* HSG37 HSE Books 1993 ISBN 0 7176 1001 2

13 *LEV Woodworking Information Sheets* WIS23, WIS24, WIS25, WIS26 HSE Books 1992

14 *The selection, use and maintenance of respiratory protective equipment: A practical guide* HSG53 HSE Books 1998 ISBN 0 7176 1537 5

15 *Selection of respiratory protective equipment suitable for use with wood dust* WIS14 HSE Books 1997

16 *Health surveillance under COSHH: Guidance for employers* HSE Books 1990 ISBN 0 7176 0491 8

17 *Occupational hygiene and health surveillance at industrial timber pre-treatment plants* WIS29 HSE Books 1994

18 *Arsenic and its compounds: Health hazards and precautionary measures* Guidance Note EH73 HSE Books 1997 ISBN 0 7176 1340 2

19 *Health surveillance and wood dust* WIS33 HSE Books 1997

The future availability and accuracy of the references listed in this publication cannot be guaranteed.

Further information

HSE priced and free publications are available by mail order from HSE Books, PO Box 1999, Sudbury, Suffolk CO10 2WA Tel: 01787 881165 Fax: 01787 313995 Website: www.hsebooks.co.uk (HSE priced publications are also available from bookshops.)

For information about health and safety ring HSE's InfoLine Tel: 08701 545500 Fax: 02920 859260 e-mail: hseinformationservices@natbrit.com or write to HSE Information Services, Caerphilly Business Park, Caerphilly CF83 3GG. You can also visit HSE's website: www.hse.gov.uk

This leaflet contains notes on good practice which are not compulsory but which you may find helpful in considering what you need to do.

This publication may be freely reproduced, except for advertising, endorsement or commercial purposes. The information is current at 9/97. Please acknowledge the source as HSE
